

VINEYARD LIGHTING

EXIT | 30L501001 WH EM



FEATURES & BENEFITS

- UNIVERSAL FIELD SELECTABLE SINGLE/DOUBLE-FACE
- WALL, END OR CEILING MOUNTED
- SUITABLE FOR DAMP LOCATIONS
- UL 924 AND CEC TITLE 20 COMPLIANT

SPECIFICATIONS

DIMENSIONS

WIDTH: 11.6"
HEIGHT: 8.2"
EXTENSION: 1.75"

FINISH

WHITE

SHADE

UNIVERSAL RED/
GREEN

LAMPING

INTEGRATED
1.2W LED

LISTING

UL DAMP

HOUSING

INJECTION-MOLDED
THERMOPLASTIC ABS
HOUSING

VOLTAGE

120/ 277V 60Hz

INPUT RATING

1.2W / 100mA

RUN TIME

90 MINUTE BATTERY
BACKUP

OPERATING TEMP

0°C to 40°C (32°F to
104°F)

CHARGING TIME

24 HOURS

BATTERY

MAINTENANCE-FREE
1.2V NI-CAD
BATTERY

JOB NAME

LOCATION

FIXTURE TYPE

QUANTITY

www.vineyardlighting.com
info@vineyardlighting.com